
CURRENT 2.0 Ampere
VOLTAGE RANG 50 to 1000 Volts

RL201 THRU RL207

DO-15\DO-204AC



Dimensions in inches and (millimeters)

FEATURES

- Low coat construction
- Low forward voltage drop
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
  260 /10 secods/.375 (9.5mm)lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.014 ounce, 0.39 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25^{O}C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	RL201	RL202	RL203	RL204	RL205	RL206	RL207	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375 (9.5mm) lead length at T_A= 50	$I_{(AV)}$	2.0							Amps
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}	30							Amps
Maximum Instantaneous Forward Voltage @2.0A	V_F	1.0							Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage per element T_A = 25	I_R	5.0							µA
T_A = 100		50							
Maximum Full Load Reverse Current, full cycle average 0.375 (9.5mm)lead length at T_L=75	$I_{R(AV)}$	30							µA
Typical Junction Capacitance (Note 1)	C_J	20							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	40							/W
Operating Junction Temperature Range	T_J	-55 to +150							
Storage Temperature Range	T_{STG}	-55 to +150							

Notes:

1. Measured at 1.0MHz and Applied Reverse Voltage of 4.0V DC.
2. Thermal Resistance from junction to Ambient at .375 (9.5mm)lead length, P.C.board mounted.

CURRENT 2.0 Ampere
VOLTAGE RANG 50 to 1000 Volts

RL201 THRU RL207

RATING AND CHRACTERISTIC CURVES RL201 Thru RL207

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

