CURRENT 1.0 Ampere
VOLTAGE RANG 50 to 1000 Volts

U1A THRU U1M


FEATURES

- For surface mounted applications
- Low profile package
- Built-in strain relief
- Easy pick and place
- Ultrafast recovery times for high efficiency
- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: SOD-123 molded plastic
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Indicated by cathode band
- Standard packaging: 12mm tape (EIA-481)
- Weight: 0.0007 ounce, 0.02 gram

SOD-123FL



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	U1A	U1B	U1D	U1G	U1J	U1K	U1M	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	800	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current .375"(9.5mm) lead length at T_L =100°C	$I_{F(AV)}$	1.0							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I_{FSM}	30							A
Maximum Forward Voltage at 1.0A	V_F	1.0			1.4	1.7			V
Maximum DC Reverse Current at T_J=25°C Rated DC Blocking Voltage T_J=125°C	I_R	10.0 100							uA
Typical Junction capacitance (Note 2)	C_J	17							pF
Typical Thermal Resistance(Note 3)	$R_{\theta JL}$	30							°C / W
Maximum Reverse Recovery Time (Note 1)	t_{rr}	50				100			ns
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-50 TO +150							°C

NOTES:1. Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, I_{rr}=0.25A
2. Measured at 1 MHz and applied V_r = 4.0 volts.
3. 8.0 mm^2 (.013mm thick) land areas.

CURRENT 1.0 Ampere
VOLTAGE RANG 50 to 1000 Volts

U1A THRU U1M

RATING AND CHRACTERISTIC CURVES U1A Thru U1M




Fig.1 FORWARD CURRENT DERATING CURVE




Fig.2 PEAK FORWARD SURGE CURRENT




Fig.3 FORWARD CHARACTERISTICS




Fig.4 TYPICAL REVERSE CHARACTERISTICS




Fig.5 TYPICAL JUNCTION CAPACITANCE